

Issuing Date 30-Jun-2015

Revision Date 30-Jun-2015

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Gatormat Trowelable Surface Mastic

Other means of identification

Product Code(s) 133

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Refer to the Product Data Sheet for Additional Information.

Uses advised against No information available

Supplier's details

Supplier Address

Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241
TEL: (513) 733-1000

Emergency telephone number

Company Emergency Phone Number (513) 733-1000

2. HAZARDS IDENTIFICATION

Classification

This product is considered hazardous by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Carcinogenicity	Category 2
-----------------	------------

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Hazard Statements • Suspected of causing cancer	Warning	
		
Appearance Brown	Physical State Liquid.	Odor Asphaltic

Precautionary Statements**Prevention**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- If exposed or concerned: Get medical attention/advice

Storage

- Store locked up.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

May be harmful if swallowed

10.9% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Asphalt	8052-42-4	25-35	*
Carbon black	1333-86-4	1-10	*
Aluminum Silicate	Proprietary	5-15	*
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	1-5	*
Quartz	14808-60-7	0.1-1.0	*
Zinc oxide	1314-13-2	0.1-1.0	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention if irritation persists.

Skin Contact Wash skin with soap and water. Get medical attention if irritation develops and persists.

Inhalation If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products Hydrocarbons. Hydrogen sulfide.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective gloves/clothing and eye/face protection.

Environmental Precautions

Environmental Precautions Dispose of contents/container to an approved waste disposal plant. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Dam up. Soak up with inert absorbent material. Use personal protective equipment. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ eye protection/ face protection Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Do not freeze. Do not store in direct sunlight or in temperatures exceeding 120°F (48.9°C). Store locked up.

Incompatible Products Strong oxidizing agents. Do not apply over chip seals or sealers containing gilsonite. Not recommended for use on portland cement, concrete or for indoor use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m ³ fume 15 min
Aluminum Silicate	TWA: 1 mg/m ³ respirable fraction	-	-

Carbon black 1333-86-4	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable fraction	30/(%SiO ₂ +2) mg/m ³ TWA, Total Dust; 250/(%SiO ₂ +5) mppcf TWA, respirable fraction; 10/(%SiO ₂ +2) mg/m ³ TWA, respirable TWA: 0.1 mg/m ³ (vacated)	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Goggles.
Skin and Body Protection Wear protective gloves/clothing.
Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid.	Appearance	Brown.
Odor	Asphaltic.	Odor Threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	7.0 - 8.0	None known
Melting Point/Range	No information available.	None known
Boiling Point/Boiling Range	100 °C	None known
Flash Point	No data available	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available.	None known
Vapor Density	No data available.	None known
Specific Gravity	1.02	None known
Water Solubility	Partly soluble.	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	No data available	None known

Flammable Properties Not flammable

Explosive Properties No data available
Oxidizing Properties No data available

Other information

VOC Content (%) No data available
 VOC (g/l) 0

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Extreme heat.

Incompatible materials

Strong oxidizing agents. Do not apply over chip seals or sealers containing gilsonite. Not recommended for use on portland cement, concrete or for indoor use.

Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons. Sulfur oxides. Hydrogen sulfide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No acute toxicity information is available for this product.
Inhalation	There is no data available for this product.
Eye Contact	There is no data available for this product.
Skin Contact	There is no data available for this product.
Ingestion	There is no data available for this product.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Asphalt	5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Carbon black	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Quartz	-	-	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization No information available.
Mutagenic Effects No information available.

Carcinogenicity This product contains crystalline silica (quartz) in a non-respirable form. Inhalation of crystalline silica is unlikely to occur from exposure to this product. Petroleum products are known to cause cancer because of carcinogenic components (e.g. benzene, DMSO). These carcinogenic components are typically found in crude petroleum products and are removed through the refinement process. This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt		Group 2B	Reasonably Anticipated	X
Carbon black	A3	Group 2B	-	X
Petroleum distillates, hydrotreated heavy naphthenic	A2	Group 1		X
Quartz	A2	Group 1	Known	X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Chronic Toxicity

No information available.

No information available.

No information available.

The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence that undiluted, air-refined asphalt is carcinogenic to experimental animals. Limited evidence exists that undiluted steam-refined and cracking residue asphalts is carcinogenic to animals. Additionally, IARC has concluded that there is inadequate evidence that asphalts alone are carcinogenic to humans.

Target Organ Effects
Aspiration Hazard

Respiratory system.

No information available.

Numerical measures of toxicity - Product**Acute Toxicity** 10.9% of the mixture consists of ingredient(s) of unknown toxicity.*The following values are calculated based on chapter 3.1 of the GHS document:***LD50 Oral** 5282 mg/kg; Acute toxicity estimate**LD50 Dermal** 3539 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not Classified

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Carbon black 1333-86-4				EC50 24 h: > 5600 mg/L (Daphnia magna)
Petroleum distillates, hydrotreated heavy naphthenic 64742-52-5		LC50 96 h: > 5000 mg/L (Oncorhynchus mykiss)		EC50 48 h: > 1000 mg/L (Daphnia magna)

Persistence and Degradability No information available.**Bioaccumulation** No information available.

Chemical Name	Log Pow
---------------	---------

Asphalt	6.006
---------	-------

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS**Waste Disposal Methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Do not re-use empty containers.

14. TRANSPORT INFORMATION**DOT** Not regulated**TDG** Not regulated**MEX** Not regulated**15. REGULATORY INFORMATION****International Inventories****TSCA** Complies**DSL** Complies**Legend****TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Asphalt	8052-42-4	25-35	0.1
Zinc oxide	1314-13-2	0.1-1.0	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc oxide		X		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Carbon black	1333-86-4	Carcinogen
Quartz	14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Asphalt	X	X	X		X
Carbon black	X	X	X	X	X
Petroleum distillates, hydrotreated heavy naphthenic				X	

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazard 1*	Flammability 1	Physical Hazard 0	Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 30-Jun-2015
Revision Date 30-Jun-2015
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet