

1. PRODUCT NAME

FixMix™

2. MANUFACTURER

Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241

Phone: 513-733-1000
Toll Free: 800-543-7077
Fax: 513-733-3989
Email: info@neyra.com
Website: www.neyra.com

- **Saves Time:** Fast, permanent repair for oil spots on parking lots.
- **Non-Shrinking:** FixMix will stay leveled and not shrink or crack, even with one inch thick applications per lift.
- **Fuel Resistant:** FixMix creates an oil resistant repair.
- **Fast-Setting:** Patches require less time before coating.
- **Versatile:** FixMix is also an excellent oil spot primer that greatly improves adhesion of coating to oil spot.

3. PRODUCT DESCRIPTION

FixMix is a high tensile strength, pigmented, water based, acrylic latex bonding agent.

Packaging:

Packaged in 1 gal. round jugs in cases of 6.

Color:

As supplied, FixMix is dark gray. Once mixed, applied and cured, FixMix is black.

Basic Uses:

FixMix is formulated to patch new or existing asphalt surfaces.

Composition:

As shipped, FixMix is an acrylic latex binder.

Limitations:

In the liquid state, FixMix must be protected from freezing and rain. Do not store in direct sunlight or where temperature exceeds 120°F.

4. INSTALLATION

Preparatory Work:

The surface must be structurally sound, surface cured and free from all loose or foreign matter prior to the application of FixMix. Priming is recommended.

To make primer, mix one part FixMix to two parts water. Allow primer to dry thoroughly before placing mix.

Methods:

Apply FixMix directly to clean, dry and primed surface. Level the patch with squeegee or screed.

Mix Design:

As supplied, FixMix is a concentrated material intended to be mixed with mortar mix.

Pour 1 gal. FixMix into a clean, empty 5 gal. pail. Add one 60 lb. bag of mortar mix while stirring thoroughly. Do not add water. Extra FixMix should only be added after thoroughly mixing. Add only as much FixMix as is necessary to achieve workable consistency. Mix only as much as can be used within one hour.

Mix Design by Volume

FixMix	Mortar	Yield
1 gal.	60 lb. bag	3 gal.

Application:

Properly mixed, FixMix will dry quickly. The following application procedures are recommended for best results:

One gal. of FixMix will make 3.0 gal. of wet mix which is enough to fill 5 sq. ft. by 1 in. deep. Coverage rates can vary with the age, texture and porosity of the pavement. Lifts up to 1 inch thick will dry in 4 hours.

As a primer, FixMix should be brushed over the prepared asphalt surface and allowed to dry thoroughly prior to application of the mixed product.

Application must be made when ambient and pavement temperatures are above 50°F. Good drying conditions are required during the subsequent 8 hours. It is recommended that the area over which the application is made be opened to use only after trial shows it to be cured sufficiently. Under good drying conditions, this usually requires about 4 hours. Lower temperatures, high humidity, clouds, shade and lack of air movement retard cure.

Precautions:

Wet FixMix must be protected at all times from freezing. Keep out of reach of children. Container should be closed when not in use. Avoid breathing vapor or contact with skin or eyes. Consult specific Neyra material safety data sheet before use.

New asphalt should be allowed to cure for a minimum of 15 days prior to application and must not exhibit ribboning, crawling, nor show oil rings when 1 gal. of clean water is poured onto the surface.

5. MAINTENANCE

Tools and equipment may be cleaned promptly with water.

6. TECHNICAL DATA

Environmental Considerations:

FixMix is non-hazardous when tested according to the EPA's TCLP (Toxicity Characteristic Leaching Procedure). FixMix is a water-based material containing less than 7 g/L (0.06 lbs/gal.) VOC content.

7. TECHNICAL SERVICES

Material safety data sheets, product and application recommendations as well as assistance with special situations and field service are available.

8. WARRANTY

The above specifications on product usage are believed to be true and accurate. Neyra Industries, Inc. guarantees that all materials manufactured comply with quality standards as described in the product data sheets. Because the application, handling, weather, workmanship and equipment are beyond the control of this manufacturer, only the quality of the products as shipped is guaranteed. In no case will the liability of Neyra Industries, Inc. exceed the purchase price of the shipped materials.

9. ADDITIONAL INFORMATION

Neyra Industries, Inc. manufactures a full line of recreational surface and asphalt pavement maintenance products as well as application equipment sold and distributed nationally at our plants and through distributors and contractors. To find the supplier most convenient to you, please contact us.

NEYRA

**Neyra Industries, Inc.
10700 Evendale Drive
Cincinnati, Ohio 45241**

**Phone: 513-733-1000
Toll Free: 800-543-7077
Fax: 513-733-3989
Email: info@neyra.com
Website: www.neyra.com**