Product Data 135-20

NEYRA[•] Professional Grade

<u>Micro Mix</u>

Trowelable Surface Mastic

I. PRODUCT NAME Micro Mix™

2. MANUFACTURER

Neyra Industries, Inc. 10700 Evendale Drive Cincinnati, Ohio 45241

Phone: 513-733-1000 Toll Free: 800-543-7077 Fax: 513-733-3989 Email: info@neyra.com Website: www.neyra.com

3. PRODUCT DESCRIPTION

Micro Mix is a blend of asphalt emulsion and fine mineral aggregate designed to fill cracks and patch asphalt pavements.

Packaging:

Available in 5 gal. pails.

Color:

Micro Mix dries black.

Basic Uses:

Micro Mix is designed as a crack filler for large cracks or minor depressions and as a surface treatment for alligatored areas on asphalt pavements.

Composition:

As shipped, Micro Mix is a blend of modified asphalt emulsion and fine graded aggregate.

Limitations:

Do not allow to freeze. Do not store in direct sunlight or where temperature exceeds 120°F. Do not apply if rain is imminent.

4. INSTALLATION

Preparatory Work:

Crack must be dry, clean, and free of dust and loose material.

Methods:

Spreadable with trowel or squeegee.

Mix Design:

Micro Mix is ready to use. No heating or dilution is required. Stir

- **Trowel Grade Performance:** Refined asphalt emulsion with small aggregate makes it a perfect trowel grade for very wide cracks.
- Workability: Can be feathered easily without losing adhesion to a sound asphalt concrete base.
- Convenient: Ready to use, no mess or loss of time mixing.
- Slate Black Color: Makes resealing unnecessary.
- Thin Set: Makes repairs possible, even on minor surface imperfections.

well before use.

•

Application:

For filling deep holes, cracks or minor depressions, a second application may be required as some shrinkage can occur. Allow a minimum of 8 hours between applications.

Precautions:

Keep out of reach of children. Container should be closed when not in use. Contains petroleum distillate. Avoid breathing vapor or prolonged contact with skin or eyes. Flush immediately with water. Consult specific Neyra material safety data sheet before use.

5. MAINTENANCE

Tools and equipment may be cleaned promptly with water.

6.TECHNICAL DATA

Environmental Considerations:

Micro Mix is considered nonhazardous when tested according to the EPA's TCLP (Toxicity Characteristic Leaching Procedure). Micro Mix is a water based material containing less than 5g/L (.08 lbs./gal.) VOC content.

7. TECHNICAL SERVICE

Material safety data sheets, product and application recommendations, as well as assistance with special situations and field service are available upon request.

8. WARRANTY

The above specifications on product usage are believed to be true and accurate. Neyra Industries, Inc. guarantees that all materials manufactured comply with quality standards as described in the product data sheets. Because the application, handling, weather, equipment and workmanship are beyond the control of this manufacturer, only the quality of the products as shipped is guaranteed. In no case will the liability of Neyra Industries, Inc. exceed the purchase price of the shipped materials.

9. ADDITIONAL INFORMATION

Neyra Industries, Inc. manufactures a full line of asphalt pavement maintenance and recreational surface products as well as application equipment sold and distributed nationally at our plants and through distributors. To find the supplier most convenient to you, please contact us.



Neyra Industries, Inc. 10700 Evendale Drive Cincinnati, Ohio 45241 Phone: 513-733-1000 Fax: 513-733-3989 Email: info@neyra.com Website: www.neyra.com