

SAFETY DATA SHEET

Issuing Date 30-Jun-2015 Revision Date 30-Jun-2015 **Revision Number** 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Jennite AE Asphalt Emulsion Pavement Sealer

Other means of identification

Product Code(s) 101

Synonyms Jennite AE Cool Weather Formula Asphalt Emulsion Pavement Sealer

Jennite AE Sand Mix Asphalt Emulsion Pavement Sealer

Recommended use of the chemical and restrictions on use

Recommended Use Refer to the Product Data Sheet for Additional Information.

Uses advised against No information available

Supplier's details

Supplier Address Neyra Industries, Inc. 10700 Evendale Drive Cincinnati, Ohio 45241

TEL: (513) 733-1000

Emergency telephone number

Company Emergency Phone

Number

(513) 733-1000

2. HAZARDS IDENTIFICATION

Classification

This product is considered hazardous by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Carcinogenicity Category 1B

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Hazard Statements May cause cancer

Danger



Appearance Brown Physical State Liquid. Odor Slight, Asphaltic

Precautionary Statements

Prevention

- · Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- · Use personal protective equipment as required.

General Advice

· If exposed or concerned: Get medical attention/advice

Storage

· Store locked up.

Disposal

• Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

2% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms Jennite AE Cool Weather Formula Asphalt Emulsion Pavement Sealer

Jennite AE Sand Mix Asphalt Emulsion Pavement Sealer

	Chemical Name	CAS-No	Weight %	Trade secret
I	Asphalt	8052-42-4	25-35	*
I	Kaolin	1332-58-7	15-25	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention if irritation persists.

Skin Contact Wash skin with soap and water. Get medical attention if irritation develops and persists.

Inhalation If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products Hydrocarbons. Hydrogen sulfide.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective gloves/clothing and eye/face protection.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Dam up. Soak up with inert absorbent material. Use personal protective equipment. Sweep

up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Wear personal protective equipment. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Keep away from open

flames, hot surfaces and sources of ignition. Do not freeze. Do not store in direct sunlight or

in temperatures exceeding 120°F (48.9°C).

Incompatible Products Strong oxidizing agents. Do not apply over chip seals or sealers containing gilsonite. Not

recommended for use on portland cement, concrete or for indoor use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m³ fume 15 min
Kaolin 1332-58-7	TWA: 2 mg/m³ particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction (vacated) TWA: 10 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Goggles.

Wear protective gloves/clothing.

Respiratory Protection If exposure limits are exceeded or irritation is experi

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area

and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Liquid. **Appearance** Brown.

Odor Slight, Asphaltic. Odor Threshold No information available.

<u>Property</u> <u>Values</u> <u>Remarks/ - Method</u>

pН 5.0 - 7.0 None known **Melting Point/Range** No information available. None known **Boiling Point/Boiling Range** 100 °C / 212 °F None known **Flash Point** No data available None known No information available. **Evaporation rate** None known Flammability (solid, gas) No data available None known

Flammability Limits in Air

upper flammability limitNo data availablelower flammability limitNo data availableVapor PressureNo data available

None known **Vapor Density** No data available. None known Specific Gravity 1.14 None known Partly soluble. **Water Solubility** None known Solubility in other solvents Partly soluble. None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known No data available **Viscosity** None known

Flammable Properties Not flammable

Explosive Properties No data available
Oxidizing Properties No data available

Other information

VOC Content (%) No data available

VOC (g/l)

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Extreme heat.

Incompatible materials

Strong oxidizing agents. Do not apply over chip seals or sealers containing gilsonite. Not recommended for use on portland cement, concrete or for indoor use.

Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO2). Hydrocarbons. Sulfur oxides. Hydrogen sulfide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product InformationNo acute toxicity information is available for this product.

InhalationThere is no data available for this product. **Eye Contact**There is no data available for this product.

Skin ContactContact with molten material will cause thermal burns.

Ingestion There is no data available for this product.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Asphalt	5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Causes burns

Delayed and immediate effects and also chronic effects from short and long term exposure

SensitizationNo information available.Mutagenic EffectsNo information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt		Group 2B	Reasonably Anticipated	X

IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic Toxicity The International Agency for Research on Cancer (IARC) has determined that there is

inadequate evidence that undiluted, air-refined asphalt is carcingoenic to experimental animals. Limited evidence exists that undiluted steam-refined and cracking residue asphalts is carcinogenic to animals. Additionally, IARC has concluded that there is

inadequate evidence that asphalts alone are carcinogenic to humans.

Target Organ EffectsRespiratory system.Aspiration HazardNo information available.

Numerical measures of toxicity - Product

Acute Toxicity 2% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 12168 mg/kg; Acute toxicity estimate LD50 Dermal 4869 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not Classified

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Asphalt	6.006

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOTNot regulatedTDGNot regulatedMEXNot regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Asphalt	8052-42-4	32.11	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Asphalt	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

	16. OTHER INFORMATION					
NFPA	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards -		
HMIS	Health Hazard 1*	Flammability 1	Physical Hazard 0	Personal Protection X		

^{*}Indicates a chronic health hazard.

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501 30-Jun-2015

Issuing Date30-Jun-2015Revision Date30-Jun-2015Revision NoteInitial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet