

SAFETY DATA SHEET

Issuing Date 30-Jun-2015 Revision Date 30-Jun-2015 Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Spec + Plus Crack / Joint Thermo-Sealant

Other means of identification

Product Code(s) 146

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Refer to the Product Data Sheet for Additional Information.

Uses advised against No information available

Supplier's details

Supplier Address Neyra Industries, Inc. 10700 Evendale Drive

Cincinnati, Ohio 45241 TEL: (513) 733-1000

Emergency telephone number

Company Emergency Phone

Number

(513) 733-1000

2. HAZARDS IDENTIFICATION

Classification

This product is considered hazardous by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Carcinogenicity Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Hazard Statements Warning

Suspected of causing cancer



Appearance Black Physical State Solid.

Odor Slight, Asphaltic

Precautionary Statements

Prevention

- · Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

· If exposed or concerned: Get medical attention/advice

Storage

· Store locked up.

Disposal

• Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

May be harmful if swallowed

0% of the mixture consists of ingredient(s) of unknown toxicity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Asphalt	8052-42-4	80-90	*
Extracts, petroleum, heavy paraffinic distillate	64742-04-7	2-5	*
solvent			

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Contact with molten materials, requires immediate medical assistance.

Skin Contact Wash off immediately with soap and plenty of water. Consult a physician. In case of burns,

immediately cool affected skin for as long as possible with cold water.

Inhalation If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Burn

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products Hydrocarbons. Hydrogen sulfide.

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective gloves/clothing and eye/face protection.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment None required.

Methods for Cleaning Up

Use personal protective equipment. Sweep up and shovel into suitable containers for

disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Wear protective gloves/ eye protection/ face protection Wash

thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Storage Keep container tightly closed in a dry and well-ventilated place. Do not store in direct

sunlight or in temperatures exceeding 120°F (48.9°C).

Incompatible Products Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt	TWA: 0.5 mg/m³ benzene soluble	-	Ceiling: 5 mg/m ³ fume 15 min
8052-42-4	aerosol fume, inhalable fraction		

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Skin and Body Protection Respiratory Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Goggles.

Wear protective gloves/clothing.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene Measures When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Solid. **Appearance** Black.

Odor Slight, Asphaltic. Odor Threshold No information available.

Property Values Remarks/ - Method

No data available pН None known 180 °C **Melting Point/Range** None known No information available. **Boiling Point/Boiling Range** None known **Flash Point** No data available None known None known **Evaporation rate** No data available Flammability (solid, gas) No data available None known

Flammability Limits in Air

upper flammability limitNo data availablelower flammability limitNo data availableVapor PressureNo data available

None known **Vapor Density** No data available. None known **Specific Gravity** 1.02 None known **Water Solubility** No data available None known Partly soluble. Solubility in other solvents None known Partition coefficient: n-octanol/waterNo data available None known No data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known Viscosity

Flammable Properties Not flammable

Explosive PropertiesNo data availableOxidizing PropertiesNo data available

Other information

VOC Content (%) No data available

VOC (g/I) 0

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons. Sulfur oxides. Hydrogen sulfide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No acute toxicity information is available for this product.

InhalationThere is no data available for this product.Eye ContactThere is no data available for this product.Skin ContactThere is no data available for this product.IngestionThere is no data available for this product.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Asphalt	5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Extracts, petroleum, heavy paraffinic distillate solvent	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

SensitizationNo information available.Mutagenic EffectsNo information available.

Carcinogenicity Petroleum products are known to cause cancer because of carcinogenic components (e.g.

benzene). These carcinogenic components may be removed during the refinement process. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt		Group 2B	Reasonably Anticipated	X
Extracts, petroleum, heavy paraffinic distillate solvent	A2	Group 1		Х

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic Toxicity The International Agency for Research on Cancer (IARC) has determined that there is

inadequate evidence that undiluted, air-refined asphalt is carcingoenic to experimental animals. Limited evidence exists that undiluted steam-refined and cracking residue asphalts is carcinogenic to animals. Additionally, IARC has concluded that there is

inadequate evidence that asphalts alone are carcinogenic to humans.

Target Organ EffectsRespiratory system.Aspiration HazardNo information available.

Numerical measures of toxicity - Product

Acute Toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity.

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral 5666 mg/kg; Acute toxicity estimate **LD50 Dermal** 2267 mg/kg; Acute toxicity estimate

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not Classified

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Asphalt	6.006
Extracts, petroleum, heavy paraffinic distillate solvent	0.5005

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOTNot regulatedTDGNot regulatedMEXNot regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Asphalt	8052-42-4	88.25	0.1

SARA 311/312 Hazard Categories

No
Yes
No
No
No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Asphalt	X	X	X		X
Extracts, petroleum, heavy paraffinic distillate solvent		Х			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION					
NFPA	Health Hazard 2	Flammability 1	Instability 0	Physical and Chemical Hazards -	
HMIS	Health Hazard 1*	Flammability 1	Physical Hazard 0	Personal Protection X	

^{*}Indicates a chronic health hazard.

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date30-Jun-2015Revision Date30-Jun-2015

Revision Note

Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet
