



# GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

## Section 1: Identification of the substance/mixture and of the company/undertaking

---

**Product form:** Liquid  
**Substance name:** GuardTop Ultra  
**Synonyms:** Polymer Modified Asphalt Based Emulsion

### Manufacturer

GuardTop LLC  
32834 Pacific Coast Highway, Suite 210  
Dana Point, CA 92629  
(877) 948-2738

### Emergency telephone number

CHEMTREC (800) 424-9300

## Section 2: Hazards identification

---

<b>Classification of the substance or mixture:</b>	Eye Irritant	Category 2A
	Skin Corrosion/Irritation	Category 2
	Respiratory/Skin Sensitizer	Category 1



**Signal Word:** WARNING

### Hazard Statements

- May cause skin and eye irritation.
- Fumes from heated material may be irritating.
- Aspiration hazard if swallowed.
- Substance may be harmful if swallowed irritating mouth, throat and/or stomach.
- Prolonged or excessive inhalation may cause respiratory tract irritation.
- Vapors may have a strong offensive odor which may cause headaches, nausea and vomiting.
- Symptoms of overexposure include: fatigue, tearing of eyes, burning sensation in the throat, cough, chest discomfort and skin irritation.

### Precautionary Statements

- Obtain and read instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Exposure to hot material may cause thermal burns.



# GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

## Section 3: Composition/information on ingredients

Chemical Name	Amount	CAS Number
Asphalt	< = 20.0%	8052-42-4
Water	< = 35.0%	7732-18-5
Aggregate Blend	< = 43.0%	14808-60-7
Carbon Black	> = 1.0%	1333-86-4
Hydrogen Sulfide	> 0.05%	7783-06-4
Cellulose Fiber	> = 1.0%	Mixture
Latex	< = 1.0 – 10.0%	Trade Secret

## Section 4: First aid measures

<b>First-aid measures general:</b>	Get prompt medical attention. Dilute with water. If solidified, treat as neat asphalt.
<b>First-aid measures after inhalation:</b>	At elevated temperatures, may cause irritation of the respiratory tract. Although this product is not known to cause respiratory problems, if breathing is difficult, safely remove victim to fresh air and provide oxygen. Get immediate medical attention.
<b>First-aid measures after skin contact:</b>	Wash skin with soap and water. Wear protective gloves to minimize skin contamination. For hot material exposure, DO NOT attempt to remove solidified material from the skin. DO NOT attempt to dissolve with solvents or thinners.
<b>First-aid measures after eye contact:</b>	Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists. Burns due to contact with heated material require immediate medical attention.
<b>First-aid measures after ingestion:</b>	Get immediate medical attention. Do not induce vomiting due to danger of aspirating liquid into lungs. Gastric lavage may be required.

### Most important symptoms and effects, both acute and delayed

<b>Eyes:</b>	Irritation
<b>Skin:</b>	Irritation
<b>Inhalation:</b>	Irritation
<b>Chronic Effects:</b>	No known hazards in normal industrial use.

## Section 5: Firefighting measures

### Extinguishing media

<b>Suitable extinguishing media:</b>	Use alcohol foam, carbon dioxide or water spray when fighting fires involving this material.
<b>Unsuitable extinguishing media:</b>	Exercise care when using water as contact with hot asphalt products - may produce steam and violent foaming.



## GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

### Special hazards arising from the substance or mixture

<b>Fire hazard:</b>	Product is an aqueous solution. Heated product may produce hazardous fumes, decomposition products or residues. Small quantities of hydrogen sulfide may be released upon heating.
<b>Explosion hazard:</b>	None
<b>Reactivity:</b>	Avoid contact with strong bases.

### Advice for firefighters

<b>Firefighting instructions:</b>	Decomposition may produce fumes, smoke, oxides of carbon, hydrocarbons and possible small quantities of hydrogen sulfide. Avoid breathing vapors from heated material. Combustion may produce CO, NO <sub>x</sub> , Sox and reactive hydrocarbons.
<b>Protection during firefighting:</b>	As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH approved and full protective gear.

## Section 6: Accidental release measures

---

### Personal precautions, protective equipment and emergency procedures

<b>General measures:</b>	Clean up spills immediately using appropriate personal protective equipment.
<b>For non-emergency personnel</b>	
<b>Protective equipment:</b>	Gloves, safety glasses, boots.
<b>Emergency procedures:</b>	Absorb spills with absorbent material. Contain spilled liquid with sand or earth.
<b>For emergency responders</b>	
<b>Protective equipment:</b>	Gloves, safety glasses, boots.
<b>Emergency procedures:</b>	Stop the source of the leak or release. Clean up releases as soon as possible.

### Environmental precautions

Prevent contamination of soil, surface water or groundwater.

### Methods for containment/clean up

Absorb spills with inert material. Contain spilled liquid with sand or earth. Contain liquid to prevent contamination of soil, surface water or groundwater. Large spillage should be dammed-off and pumped into containers.



# GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

## Section 7: Handling and storage

---

### Precautions for safe handling

- Shelf Life:** 30 Days @ 77 degrees C (in original, sealed containers).
- Additional hazards when processed:** When handling hot material, use protective clothing impervious to this material.
- Precautions for safe handling:** Use good Hygiene measures: wash exposed areas with mild soap and water before eating, drinking or smoking and again when leaving work.
- Storage conditions:** Do not store at temperatures above 82 degrees C.

## Section 8: Exposure controls/personal protection

---

- Engineering Controls:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.
- Eye/Face Protection Requirements:** Where contact with this material is likely, eye protection is recommended.
- Skin Protection Requirements:** Selection of specific items such as gloves, boots, apron or full-body suit will depend on operation and potential exposure.
- Respiratory Protection Requirements:** Where there is potential for airborne exposure in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

### Exposure Guidelines:

- Hydrogen Sulfide:** NIOSH REL C 10 ppm, 15 mg/m3 (10 min.)  
OSHA PEL C 20 ppm, 50 ppm (10 min.)



## GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

### Section 9: Physical and chemical properties

---

#### Information on basic physical and chemical properties

<b>Physical state:</b>	Liquid
<b>Appearance:</b>	Brown to Black
<b>Odor:</b>	Asphalt Odor
<b>pH:</b>	10-11.5
<b>Melting point:</b>	0 C
<b>Freezing point:</b>	0 C
<b>Specific Gravity:</b>	1.4-1.7 (Water=1)
<b>Boiling point:</b>	100 degrees C @ 760 mm Hg
<b>Flash point:</b>	None
<b>UEL:</b>	N/A
<b>LEL:</b>	N/A
<b>Vapor pressure:</b>	Same as water mm Hg @ 21 degrees C
<b>Solubility:</b>	Soluble in water
<b>%Volatiles:</b>	<35% @ 21 degrees C @ 760 mm Hg
<b>VOC:</b>	<1

### Section 10: Stability and reactivity

---

<b>Reactivity:</b>	Low
<b>Chemical stability:</b>	This compound is stable at ambient conditions.
<b>Possibility of hazardous reactions:</b>	Low
<b>Conditions to avoid:</b>	Avoid extreme temperatures.
<b>Incompatible materials:</b>	Avoid contact with strong bases.
<b>Hazardous decomposition product:</b>	Decomposition will not occur if handled and stored properly.
<b>Polymerization:</b>	Hazardous polymerization will not occur.



# GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

## Section 11: Toxicological information

---

<b>Skin corrosion:</b>	May cause irritation and a rash with prolonged or repeated contact with skin.
<b>Serious eye damage/irritation:</b>	Irritating, may injure eye tissue if not removed promptly.
<b>Respiratory or skin sensitization:</b>	Repeated contact may cause skin irritation, prolonged inhalation may cause respiratory tract irritation.
<b>Germ cell mutagenicity:</b>	None
<b>Carcinogenicity:</b>	<p>IARC No components of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.</p> <p>ACGIH No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.</p> <p>NTP No components of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.</p> <p>OSHA No components of this product present at levels greater than or equal to 0.1% is identified as carcinogen or potential carcinogen by OSHA.</p>
<b>Reproductive toxicity:</b>	This product contains one or more chemicals known to cause reproductive harm.
<b>Specific target organ toxicity (single exposure):</b>	Skin and/or respiratory irritation, mild.
<b>Specific target organ toxicity (repeated exposure):</b>	Skin, respiratory, kidney and liver.
<b>Aspiration hazard:</b>	Respiratory distress as a result of aspiration.
<b>Symptoms/injuries after inhalation:</b>	Respiratory tract irritation, cough, chest discomfort.
<b>Symptoms/injuries after eye contact:</b>	Eye tearing, irritation, burns if contact made with heated material.
<b>Symptoms/injuries after ingestion:</b>	Harmful if swallowed, irritating to mouth, throat and stomach.

## Section 12: Ecological information

---

### Environmental Hazards

This material should be prevented from uncontrolled applications to soil or earth. This material should be prevented from entering storm water, sewage drainage systems and bodies of water.



## GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

### Section 13: Disposal considerations

---

***Waste Disposal:***

This product, as supplied, when discarded or disposed of, may be a hazardous waste according to Federal regulations (40 CFR 261). Under the Resource Recovery Act (RCRA), it is the responsibility of the user of the product to determine whether the material is a hazardous waste subject to RCRA. Treat or dispose of waste material in accordance with all local, state/provincial and national requirements. Avoid disposal into wastewater treatment facilities.

***Contaminated Materials:***

Treat as product waste.

***Container Disposal:***

Unclean empty containers should be disposed of in the same manner as the contents.



# GuardTop® Ultra High Performance Sealcoat Safety Data Sheet

## Section 14: Transport information

---

<b>Product Label:</b>	GuardTop Ultra Asphalt Based Emulsion
<b>UN Number:</b>	Non-hazardous, no UN number
<b>DOT Shipping Name:</b>	Non Regulated, Water Based Asphalt Emulsion
<b>DOT Hazard Class:</b>	Non-Hazardous

## Section 15: Regulatory information

---

<b>EEC Symbols and Indications of Danger:</b>	Irritant (Xi)
<b>R-Phrases:</b>	R36/37/38 – Irritating to eyes, respiratory system and skin.
<b>WHMIS Hazard Symbols:</b>	Class D – Irritant
<b>CERCLA Hazardous Substances:</b>	HYDROGEN SULFIDE (CAS 7783-06-4) – RQ 100 lb.
<b>California Proposition 65:</b>	This product contains one or more chemicals known to the State of California to cause cancer and/or reproductive harm.
<b>Clean Air Act – Section 112:</b>	
<b>Title V:</b>	HYDROGEN SULFIDE (7783-06-4)
<b>SC Toxic Air Pollutants List:</b>	HYDROGEN SULFIDE (7783-06-4)
<b>Sara Title II – Section 313:</b>	There are no known ingredients subject to reporting.
<b>TSCA Inventory Status:</b>	All ingredients of this product are listed.

## Section 16: Other information

---

### Indication of changes

<b>NFPA health hazard:</b>	1
<b>NFPA fire hazard:</b>	0
<b>NFPA reactivity:</b>	0
<b>Personal Protection Index:</b>	1

### HMIS III Rating

<b>Health:</b>	1
<b>Flammability:</b>	0
<b>Reactivity:</b>	0
<b>Special Hazard:</b>	None

**IMPORTANT:** The information presented herein, while not guaranteed, is true and accurate to the best of our knowledge. **NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE.** This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and GuardTop LLC. assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer.